PM811N-G2

Power Supply Switch Mode, 12 VDC, 1 A, EN Grade 2

Certified Gr.2

Suitable for use in systems designed to comply with EN50131-6:2008 Grade 2 and Environmental Class II requiring 8 Ah standby battery capacity.

Protection

Comprehensive protection is built-in as standard including mains transient filtering, electronic output overload protection and fuses on the load and battery outputs.



Details

- Fault signals for loss of mains, power supply fault and battery low voltage warning
- Battery deep discharge protection
- Tamperswitch
- Protection against reverse battery connection
- LED's for comprehensive diagnostics
- Thermal protection of power circuitry
- Powder coated steel housing
- EN50131-6:2008 Grade 2 Type A certified

PM811N-G2

Power Supply Switch Mode, 12 VDC, 1 A, EN Grade 2

Technical specifications

General

Fuse(s)	Load: F1.0 A, Batt: F1.0 A
Deep discharge protection	Battery disconnect @ 10.6 V battery terminal voltage
Protection	Reverse battery connection protection

Electrical

Mains input	100 to 240 VAC

Output

Power output voltage	13.8 VDC
Output ripple	<400 mV pk-pk max. @ rated voltage
Power output current mains	1 A

Battery

Max. Battery capacity	8 Ah, 12 V
Power output current battery	12 h, 0.6 A with 8 Ah battery
Battery recharge time	<72 h to 80%

Physical

Physical dimensions	230 x 200 x 80 mm (W x H x D)
Net weight	2 kg (without battery)
Colour	White
Form factor	Steel cabinet
Housing (steel) powder coated	1.2 mm

Environmental

Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C
Environment	EN50130-5 ; Class II - Indoor (general)

Regulatory

EN50131 Grade	Grade 2
Compliancy	CE, REACH, RoHS 2, WEEE
Certification	EN50131 Grade 2
Certifications	EN50131-6:2008 Grade 2 Type A

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 15:17