# ATS1180M

**Lecteur de cartes sécurisé MIFARE DESFire EV1/EV2/EV3 avec sortie et entrée RTE dans un design fin, conçu pour les solutions mobiles.**

## Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel using the ATS databus. Communication to Advisor Advanced control panels is AES encrypted. In secure mode, card to reader data is also AES encrypted providing secure communication from the card to the processing unit. The readers are configured locally through keypad and control panel menu and the address is configures using the ATS1482 addressing card. Select secure cards from the ATS145x secure card series. The reader is also prepared to support future mobile credentials.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS118xM Mifare Desfire readers are designed to transfer card data in a secure and reliable way in various environments. The card data is by default secured by an Aritech own security key, but can be changed easily in Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

## Communication

The reader communicates in a secure way over the Advisor databus to Advisor control panels using AES encryption, securing the data from the card until being processed.

## Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.
Mounting brackets and weather protection covers provide extend the available applications.



## Détails

- Lecteur Secure ATS MIFARE DESFire EV1/EV2/EV3
- Préparé pour l'accréditation mobile à l'aide du Bluetooth
- Prend en charge Secure Mifare (mode sécurisé) ou Mifare 4 ou 7 octets CSN/UID (mode non sécurisé).
- Utiliser des cartes sécurisées de la série ATS145x ou des cartes clients
- Communication sécurisée par cryptage AES-128 bits entre le lecteur et la centrale Advisor Advanced / CDC4
- Boîtier robuste en plastique moulé au design fin
- Montage en intérieur ou en extérieur
- Interface bus ATS
- Entrée de demande de sortie
- Sortie à collecteur ouvert (porte ouverte)
- Pris en charge à partir de Advisor Advanced MR4.9 et Axon MR1.0
- NFC préparé à des fins de configuration

# ATS1180M

## Lecteur de cartes sécurisé MIFARE DESFire EV1/EV2/EV3 avec sortie et entrée RTE dans un design fin, conçu pour les solutions mobiles.

## Spécifications techniques

### System

| | |
|---|---|
| Reading distance | Secure: max. 2 cm<br>Unsecure: max. 5 cm<br>Bluetooth depending on mobile device and settings |
| Max. reader distance to panel | 1500 m |
| CSN (Card Serial Number) | Yes |
| Custom data model | Yes |
| Supported card types | MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3 |
| Addressing type | Kartenadressierung |
| No. of LEDs | 3 |

### Technology

| | |
|---|---|
| Reader type | Smartcard |
| Reader operating-transmitting frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (benutzerdefinierte Daten), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (Benutzerdefinierte Daten), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data) |
| Mifare type | ISO14443A |
| No. of Mifare bytes CSN | 4 Byte (nicht eindeutig), 4 Byte (S50), 7 Byte (S50), 7 Byte (S70) |

### Interface & connections

| | |
|---|---|
| Interface | ATS RS-485 |
| Connector type | Zopf |
| Pigtail length | 2 m |

### Inputs/outputs

| | |
|---|---|
| Inputs | Aufforderung zum Beenden |
| Outputs | 1 Open Collector (10 mA) |

### Tamper type

| | |
|---|---|
| Pry-off tamper | Yes |

### Operation

| | |
|---|---|
| Stand-alone | No |
| PIN keypad | No |

### Electrical

| | |
|---|---|
| Operating voltage | 10.8 to 30 VDC |
| Current consumption | 55 mA @13.8 VDC normal<br>85 mA @13.8 VDC max. |

### Physical

| | |
|---|---|
| Physical dimensions | 140 x 44 x 20 mm |
| Net weight | 240 g |
| Shipping weight | 275 g |
| Colour | Schwarz |
| Material | Plastik |
| Form factor | Slimline |
| Mounting Type | Oberflächenmontage |

### Environmental

| | |
|---|---|
| Operating temperature | -40 to +55°C |
| Storage temperature | -40 to +55°C |
| Relative humidity | <95%, noncondensing |
| Environment | Drinnen, Draussen |
| IP rating | IP67<br>IK09 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57