RF-DC101B-K4

Trasmettitore universale con contatto magnetico Wireless, marrone, 433Mhz, 80plus LoNa

In this series we are using KGS's 80+ wireless protocol in a 433Mhz frequency set-up, which allows for a better wireless indoor range. This 80+ protocol also helps ensure security approvals.
This wireless door window sensor, which has 2 reed switches, protects anything that opens and closes such as doors, windows and cabinets. You can monitor any supervised contact in such a way that hardwired devices become wireless in a fraction of time.
The sensor is equipped with a wall and cover tamper for additional security.
This series comes in a white and a mahogany version and also has accessories in both colors.



Dettagli

- 80+ wireless protocol using 433Mhz for improved indoor range
- 5-years battery life
- Battery pull-tab concept
- Selectable reed switches
- Additional terminal block
- Range of accessories : two types of spacers and a stronger magnet
- Holding EN and Incert certificates

RF-DC101B-K4

Trasmettitore universale con contatto magnetico Wireless, marrone, 433Mhz, 80plus LoNa

Specifiche tecniche

General

Application type	Oberflächenmontage
Contact type	Reed switch

Wired/wireless

Wired-wireless	Drahtlos
Wireless frequency	433 MHz LoNa
Open-air range	400 m

Electrical

Battery lifetime	> 5 Jahre mit Supervis. Signal pro 15 Min. und 4 Aktivierungen/Stunde

Physical

Colour	Mahagoni

Regulatory

EN50131 grade	Klasse 2

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57