SC-31-0200-0001-99

SmartCell White Sounder

Overview

The SmartCell Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-31-0200-0001-99
SmartCell White Sounder

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	SmartCell, Excellence Gateway

Electrical

Batteries	3 x 3.6 V lithium thionyl chloride batteries. Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)

Sounder

Output level	95 dB(A) at 1 m max.
Output level adjustment	High or low
Selectable tones	32

Physical

Physical dimensions	110 x 72 mm (Ø x D)
Net weight	0.2 kg
Colour	Hvid
Mounting type	Vægmontering
Mounting position	Pared

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
IP rating	Type B: for indoor/outdoor use (IP33)

Regulatory

Compliancy	CE
Certification	CPR
Standards	EN54-3 EN54-13 EN54-25

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 30 July 2026 - 10:04