SC-33-0230-0001-99

Information White Sounder and Ceiling Visual Indicator (Blue Flash)

Overview

The SmartCell Information Sounder and Visual Indicator is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include visual indicator (blue flash), 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Includes visual indicator (blue flash)
- Unique design
- Inbuilt locking mechanism
- NOT FOR FIRE OR SECURITY APPLICATIONS

SC-33-0230-0001-99

Information White Sounder and Ceiling Visual Indicator (Blue Flash)

Technical specifications

General

Wireless frequency	868 MHz

Electrical

Batteries	3 x 3.6 V lithium thionyl chloride batteries. Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)

Sounder

Output level	92 dB(A) at 1m max.
Output level adjustment	High or low
Selectable tones	32

VID

Colour	Blue flash
Flash frequency	0.5 Hz (1 flash, every 2 seconds)

Physical

Physical dimensions	110 x 94 mm (Ø x D)
Net weight	0.2 kg
Colour	Hvid

Environmental

Operating temperature	-10 to +55 °C
Storage temperature	-10 to +30 °C (with batteries) -10 to +55 °C (without batteries)
Relative humidity	0 to 95% noncondensing
Environment	Indendør
IP rating	IP21C

Regulatory

Compliancy	CE
Certification	CPR
Standards	EN54-13

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 April 2026 - 13:15