# BS130N

**Droge accu, 12 V, 12 Ah, VdS**




## Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS130N

## Droge accu, 12 V, 12 Ah, VdS

## Technische specificaties

### General

| | |
|---|---|
| Product type | Forseglet blybatteri |

### Electrical Characteristics

| | |
|---|---|
| Nominal voltage | 12 V |
| Nominal capacity | 12 Ah |
| Internal approx. resistance | 13 mOhm |

### Charge / discharge

| | |
|---|---|
| Max. charge voltage | 13.8 VDC at +20°C |
| Max. charge current | 3.6 A |
| Max. discharge current | 60 A |

### Temperature

| | |
|---|---|
| Charging temperature | 0 to +40°C |
| Discharging temperature | -15 to +50°C |

### Physical

| | |
|---|---|
| Material | ABS |
| Terminal type | Fast-on 6.35 mm |

### Environmental

| | |
|---|---|
| Fire retardant | No |
| Storage temperature | -15 to +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS 2, WEEE |
| Certification | VdS |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57