# ATS1188

**Secure MIFARE DESFire EV1/EV2/EV3 card reader with output and RTE input in slim design, compatible with mobile credential, Aritech ID (Bluetooth).**

## Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel using the ATS databus. Communication to Axon and Advisor Advanced control panels is AES encrypted. In secure mode, card to reader data is also AES encrypted providing secure communication from the card to the processing unit. The readers are configured locally through keypad and control panel menu and the address is configures using the ATS1482 addressing card. Select secure cards from the ATS145x secure card series. The reader is also prepared to support future mobile credentials.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS118xM Mifare Desfire readers are designed to transfer card data in a secure and reliable way in various environments. The card data is by default secured by an Aritech own security key, but can be changed easily in Axon or Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

## Communication

The reader communicates in a secure way over the ATS LAN databus to Axon or Advisor control panels using AES encryption, securing the data from the card until being processed.

## Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.
Mounting brackets and weather protection covers provide extend the available applications.




## Details

- Secure ATS MIFARE DESFire EV1/EV2/EV3 reader
- Compatible with Mobile credential Aritech ID.
- Supports Secure Mifare (secure mode) or Mifare 4 or 7 byte CSN/UID (Unsecure mode)
- Use secure ATS145x series cards or customer cards
- Secure communication using AES-128 bits encryption between reader and Advisor Advanced / Everon panel
- Robust molded plastic housing in slim design
- Indoor or outdoor mounting
- ATS bus interface
- Request To Exit input
- Open Collector Output (door open)
- Supported as of Advisor Advanced from MR4.13 and Everon MR4.3
- NFC prepared for configuration purposes

# ATS1188

## Secure MIFARE DESFire EV1/EV2/EV3 card reader with output and RTE input in slim design, compatible with mobile credential, Aritech ID (Bluetooth).

## Technical specifications

### System

| | |
|---|---|
| Reading distance | Secure: max. 2 cm<br>Unsecure: max. 5 cm<br>Bluetooth depending on mobile device and settings |
| Max. reader distance to panel | 1500 m |
| CSN (Card Serial Number) | Yes |
| Custom data model | Yes |
| Supported card types | MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3 |
| Addressing type | Adresowanie kartą |
| No. of LEDs | 3 |

### Technology

| | |
|---|---|
| Reader type | Smart Card |
| Reader operating-transmitting frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (własne dane), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (Własne dane), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data) |
| Mifare type | ISO14443A |
| No. of Mifare bytes CSN | 4 bajty (nie-unikalny), 4 Bytes (S50), 7 bajtów (S50), 7 Bytes (S70) |

### Interface & connections

| | |
|---|---|
| Interface | ATS RS-485 |
| Connector type | Svinesvans |
| Pigtail length | 2 m |

### Inputs/outputs

| | |
|---|---|
| Inputs | Przycisk wyjścia |
| Outputs | 1 Open Collector (50 mA) |

### Tamper type

| | |
|---|---|
| Pry-off tamper | Yes |

### Operation

| | |
|---|---|
| Stand-alone | No |
| PIN keypad | No |

### Electrical

| | |
|---|---|
| Operating voltage | 10 to 30 VDC |
| Current consumption | 50 mA @13.8 VDC normal<br>120 mA @13.8 VDC max. |

### Physical

| | |
|---|---|
| Physical dimensions | 126 x 85 x 28 mm |
| Net weight | 240 g |
| Shipping weight | 275 g |
| Colour | Sort |
| Material | Plastic |
| Form factor | Slimline |
| Mounting Type | Montaż nawierzchniowy |

### Environmental

| | |
|---|---|
| Operating temperature | -30 to +55°C |
| Storage temperature | -30 to +55°C |
| Relative humidity | <95%, noncondensing |
| Environment | Indendør, Udendørs |
| IP rating | IP67<br>IK09 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:23