IU2055NC

Unité de contrôle de zone conventionnelle de la série 2000 d'Aritech.

Product overview

The IU2055NC is and addressable, 2000 Series two-wire zone monitor designed to provide an interface between conventional fire detectors and an addressable 2000 series protocol fire alarm control panel. The IU2055NC enables the addressable panel to monitor the presence and operation of up to 30 conventional detectors in standard or up to 20 in intrinsically safe configurations.

Application

The IU2055NC allows for the upgrade and inclusion of an existing or new conventional fire zone into and addressable detection loop. It supervises the conventional zone circuit for open and short circuits and monitors it for alarm conditions. Any abnormal conditions are reported to the control panel and are indicated on the IU2055NC with a yellow LED. The unit supports alarm verification and CleanMe™. It resets by cycling power to the zone circuit as directed by the fire panel.

Operation

The IU2055NC is connected to the panel via a two wire communication loop that provides power and carries control and input data. The module address is easily set with two rotary switches. The address setting is non-volatile and will not be lost in the event of a power failure.

The 2000 series conventional zone monitor utilizes an advanced digital data communications protocol that ensures the integrity of the data communication with extensive error correction algorithms.



Détails

- Contrôle jusqu'à 30 détecteurs conventionnels standard ou jusqu'à 20 détecteurs conventionnels à sécurité intrinsèque
- Zone surveillée pour les circuits ouverts et les courts-circuits
- Prise en charge de la vérification des alarmes et des fonctions CleanMe™
- Alimenté par une boucle
- Adressage numérique facile
- Prise en charge des applications standard et à sécurité intrinsèque
- Certifié CE/CPR selon EN54:18

IU2055NC

Unité de contrôle de zone conventionnelle de la série 2000 d'Aritech.

Spécifications techniques

General

Status indication	Alarm LED, Fault LED
Compatibility	2000 Series Systems
Addressing method	Rotary switch
Address range	1 to 128

Electrical

Power supply type	Zasilanie pętlą
Operating voltage	21 to 28 VDC (loop) 17.5 to 18.5 VDC (zone)
Current consumption	<15 mA (standby) <40 mA (alarm) <3.6 mA (remote indicator)

Input

Input quantity	1
Input type and rating	Supervised, 19.4 mA max.
Input states	Aktywny, Normal, Otwarty, Zwarty
Supervisory voltage	17.5 to 18.5 VDC
Termination resistor	3.9 kΩ, ¼ W, 5%
Zone resistance - normal mode	<40 Ohm
Zone resistance - intrinsic safe mode	<26 Ohm

Output

Output quantity	1 (remote indicator)
Output type and rating	Unsupervised, 3.6 mA

Physical

Physical dimensions	175 x 124 x 51 mm
Net weight	325 g
Colour	Weiß
Mounting type	Wandmontage
Cable entries	1
Material	Plastik
Cable specification	J-Y(ST)Y 2x2x0,8 rt, EB CY (TP) 2x2x0,75, KAL21A, KAL21B, KAL51A, KAL51B, KAL61A

Environmental

Vandal proof	No
Operating temperature	−10 to +55°C
Storage temperature	−20 to +60ºC
Relative humidity	10 to 95% noncondensing
Environment	Drinnen, IS
IP rating	IP40

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR
Standards	EN54-18

Produits compatibles

Catégorie	Référence	Description
Detection device	ISM-95	2000/900 Series Isolator Module w/ CPD Housing
Interface unit	IO2034NC	2000 Series 4 input and 4 output unit
Interface unit	IU2050NC	2000 Series IO Unit 1 In
Interface unit	IU2080NC	Signalgebermodul der 2000er Serie, inkl. Gehäuse

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57