AS376

Fire Sounder, Multi Tone, High Output, IP66

General

The AS376 is a high output electronic sounder for fire alarm applications. It offers a IP66 rating, which makes it ideal for outdoor applications. It also features a special base containing all wiring connections and allow for easy removal/placement of the sounder. To allow for even more flexibility, the user can select between 64 tones and also have the option of a 3rd stage tone.

Easy and Fast Installation


The AS376 sounder allows faster installation and maintenance thanks to an innovative mounting base. Connections are made to the base during the initial wiring phase, which results in faster and more reliable installation. In addition, the head clicks into place and is fixed by four quarter turn fasteners, avoiding the need to screw up four individual screws thus enabling faster installation and accurate seal compression for weatherproofing.

Efficient and versatile

The AS376 provide high sound output at a low current, thus reducing power requirements and system cost. The AS376 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation.

With a choice of 64 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second and third tone, is available if extra wires are installed in the sounder circuit.

IP66 as standard, means that the AS376 can be installed in almost any location.



Details

- High sound output
- Low current consumption
- 64 Tones user selectable
- Automatic syncronisation
- Volume control
- Wiring directly to base
- Three stage alarm
- IP66

AS376

Fire Sounder, Multi Tone, High Output, IP66

Technical specifications

General

Line monitoring	Polarised input

Electrical

Operating voltage	17 - 60 VDC (EN54-3 / fire applications) 10 - 60 VDC (non-fire applications)
Current consumption	10 - 50mA @ 24 VDC ((see tone table in manual))

Sounder

Output level	Sound output at 1 m (see tone table in manual): 104 to 116dB(A) @ 24 VDC Continuous operation
Selectable tones	64
Synchronization	Phased start (automatic)

Physical

Physical dimensions	166 x 166 x 149 mm (W x H x D)
Net weight	1100 g
Colour	Rød
Material	Alto impacto policarbonato

Environmental

Operating temperature	-25 to +70°C
Environment	Udendørs
IP rating	IP66

Regulatory

Certification	EN54-3

EDWARDS
Built for Resilience

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 October 2026 - 11:45