ATS1700-MM

Panel Everon 1700, IP integrado, Grado 3, Web App, de 8 a 32 zonas, 4 áreas, carcasa metálica, multilingüe

Axon, More at the Core

Axon is at the core of the complete security solution that you need. It offers exceptional integration, capability, reliability, installation and user experience. With Axon your security solution is connected to UltraSync Connected Services, through a fully secure cloud solution.

Exceptional integration

Axon is backwards compatible and easy to migrate from legacy systems, including Advisor Advanced. It offers new APIs, allowing a seamless integration with 3rd party systems. For an even more complete solution, the video surveillance of Aritech is added to the Axon solution via the UltraSync ecosystem.
All Advisor Advanced panels provide integrated access can control where end-user can be grouped. Each group has a separate definition for doors accessible as well as when access is allowed. Being a truly integrated system, additionally users can disarm areas when access to a door is granted.

Exceptional capability

Axon supports up to 1000 intrusion zones, with an optimized cable management system and more power per zone. Axon can handle up to 112 access doors, has a new GSM module for connectivity, cloud applications for remote management and diagnosis through UltraSync.

Exceptional reliability

Axon is built upon the successful Advisor Advanced panel: it delivers the highest standard of reliability. With strong cybersecurity levels, Axon is constantly updated based on today's needs.

Exceptional installation

Axon has an exceptional installation, thanks to its multiple tools to make it easy to install: configuration through web browser, new configuration wizards, on-premises or off-premises configuration and incident management, high scalability through the configurator making it more adaptable whether for challenging buildings, extensions or changes of use, and finally, the ability to save and replicate configurations.

Exception User eXperience

Axon provides an optimal user experience with an enriched UX via a new controller platform integrating intrusion, access & video. The user interface has a new contemporary design, including a web application and a touchscreen making it more intuitive and faster to configure. Finally, the panel design has been revisited to fit a new family look across Aritech new generation of products such as the keypad and the upcoming detectors.

Integration to the UltraSync Connected Services ecosystem



Detalles

- 8 zonas en placa
- Max. 48 zonas: cableadas, inalambricas o mixtas
- Expansores de entradas y salídas enchufables
- Hasta 16 entradas para sensor de vibración
- 4 areas
- Hasta 2000 usuarios sin controlador de accesos y hasta 65532 con controlador de accesos
- Puerto USB para configuración local
- Multilenguaje - idioma independiente para los 2000 usuarios
- Reportes de alarma por IP a receptora OH-NETREC (GPRS/3G/4G opcional)
- Conexión Ethernet 10/100 Mb integrada
- Control de accesos estandar sin controladores de puertas
- Control de accesos total con controladores de puerta CDC4(-EN)
- Auto armados - calendarios - salidas temporizadas
- Chequeo del estado del panel en vivo o programado a traves de UltraSync para sistemas registrados
- Configuración utilizando Web Browser en movil, tablet o PC
- Conectores extraibles con codigo de colores
- Compatibilidad con Advisor Advanced
- Fuente de alimentación inteligente
- Bus de datos de alta velocidad

We know that the cloud services are the current wave to surf on, and we also believe that it’s the solution to provide you with a multitude of exceptional services, that are secure and easy to handle, for an optimized security system. This is why the UltraSync Connected Services universe is key to our complete range of products, and of course Axon. The connection to UltraSync provides a cloud configurator, cloud backup and restore, external API, firmware upgrade, user management and much much more.

ATS1700-MM

Panel Everon 1700, IP integrado, Grado 3, Web App, de 8 a 32 zonas, 4 áreas, carcasa metálica, multilingüe

Especificaciones técnicas

System

Product line	Everon
Product type	Integrierte Zugangskontrolle
Panel type	Hybrid
Kit	No
No. of keypads / readers	8
Data Gathering Panels (DGP)	7
No. of alarm groups	256
Specified cable	WCAT52 / WCAT54 o equivalente

Inputs

Max no. of inputs	48
Onboard inputs	8
Inputs plug-in expansion	8
ATS1202 support	3

Outputs

No. of outputs	128
No. of onboard outputs	3 salidas electronicas + 1 rele

Area

No. of areas	4

User/Cards

Max. no. of users	Up to 65532
Users with name	1000
Max. no. of cards	De 2000 a 65532
Max. no. of PIN codes	De 2000 a 65532

Access control

Standard doors on control panel	4
Door groups	128
Floor groups	128
Intelligent doors on 4-door DGPs	28

Communication

Onboard transmission type	IP
Transmission extension	GSM, GSM/GPRS, GSM/GPRS/IP, IP
Databus type	RS485

Event log

Alarm event log	14500
Access event log	10000

Electrical

Operating voltage	24 VDC
Power supply type	230 VAC
Power supply value	230 VAC, -10 a +15%, 50 Hz
Current consumption	650 mA max. a 230 VAC
Mainboard current consumption	110 mA a 24 V (PSU), 160 mA a 12 V (bateria)
Max system current	950 mA a 13.8 V ±0.2 V
Max aux power current	2500 mA a 13.8 VDC ±0.4 V
Auto-reset fuses	3 (electronicos)
Glass break fuses	1 (Alimentación principal, T-2A 230 VAC)

Physical

Physical dimensions	315 × 388 × 85 mm
Net weight	4.9 kg (sin bateria)
Colour	Weiß
Material	Stahl (lackiert)
Housing	Metal medio

Environmental

Operating temperature	-10 a +55°C
Relative humidity	95% sin condensación
Environmental Class	Class II, interior
IP rating	IP31

Regulatory

EN50131 Grade	Grado 3, con kit sabotaje
Compliancy	CE
Certification	CE, EN50131 Grado 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57