# AS36RIM

## Sounder Beacon Rim with "Fire" text (English)

### General

The AS36RIM is an aesthetic surround AS360, AS2360, FA360 and FA2300 series VADs, visual indicators, sounders and combination units. It allows for the selected product to be displayed with "FIRE" text, in the selected language.

The AS36RIM may be retro fitted to compatible deep base devices in the range, and allows for convenient and clear visual verification of the location of fire notification equipment on any installation.




### Installation

Due to an innovative design, the text orientation of the AS36RIM may either be horizontal or vertical, depending on the application requirements. A locking mechanism prevents the orientation position from being changed once the notification device has been installed.

Designed to accommodate both surface and rear cable entry, the selected, deep base notification device continues to maintain its IP rating as before. The AS36RIM in no way affects the operation or mounting options of the selected notification device, and may be used for compatible addressable and conventional notification devices.

### Additional text

Because of the flat surface areas, logos and/or additional text may be added on site as required.

### Detaljer

- Easy to install
- Provides and aesthetic surround for fire notification devices
- Horizontal or vertical installation
- Locking mechanism to lock orientation
- Additional flat surfaces for logos or text

# AS36RIM

## Sounder Beacon Rim with "Fire" text (English)

## Tekniska specifikationer

### Physical

| | |
|---|---|
| Colour | Rød |
| Mounting type | Vægmontering |
| Mounting position | Parede |
| Material | Alto impacto policarbonato |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Environment | Indendør, Udendørs |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 2 |

### Kompatibla produkter

| Kategori | Referens | Beskrivning |
|---|---|---|
| Notification device | AS363 | Röd siren med låg sockel 32 toner, IP21 för CPD-godkänd 17-60 VDC, 4-41 mA. Spänningsmatning 9-60 VDC, 4-41 mA, 90-106 dBA vid 1 m |
| Notification device | AS363W | Vit siren med låg sockel 32 toner, IP21 för CPD-godkänd 17-60 VDC, 4-41 mA. Spänningsmatning 9-60 VDC, 4-41 mA |
| Notification device | AS364 | Röd siren med lhög sockel 32 toner, IP65 för CPD-godkänd 17-60 VDC, 4-41 mA. Spänningsmatning 9-60 VDC, 4-41 mA, 90-106 dBA vid 1 m |
| Notification device | AS364M | Sounder, Multi Tone, Deep Base, Mains Powered |
| Notification device | AS364W | Fire Sounder, Multi Tone, Deep Base, White |
| Notification device | AS366 | Siren med låg sockel och blixtljus |
| Notification device | AS367 | Siren med hög sockel och blixtljus |

EDWARDS
Built for Resilience

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57